# MOMENTA RX7 SEMI SYNTHETIC

### PRODUCT DESCRIPTION:

Momenta RX7 is semi synthetic diesel engine oil designed for the most severe performance requirements of highly powered turbocharged engines of leading automobile companies. This oil is fuel saving and reduces maintenance expenses for machines and engines. It resists oil thickening and the formation of carbon, varnish and sludge deposits. It also helps prolong engine life.

## APPLICATION:

Recommended for modern heavy-duty engines, wide range of turbo-charged or naturally aspirated diesel engines as well as all kinds of gasoline engines, generators, trucks, construction cars, passenger cars or mixed car group comprising diesel and gasoline cars. The oil is suitable for high speed, four stroke cycle diesel engines used on heavy-duty applications. This oil is also an excellent choice for mixed fleet services.

### FEATURES & BENEFITS:

- Extended drain intervals.
- Resists oil thickening and the formation of carbon, varnish and sludge deposits.
- Good viscosity stability.

- Prolonged engine life.
- Properly balanced detergency and dispersancy ensures a clean engine.

## PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CG-4/SJ
- DTFR 15B110
- ACEA A3/B4

- VOLVO VDS
- MTU Type-2
- MACK EO-L
- MAN 3275 Allison C4

## TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	MOMENTA RX7	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.6
Viscosity Index (min)	D2270	-	145	145
SP. Gravity @15°C/60°F	D4052	g/cm³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36
TBN	D2896	mg KOH/g	9.5	9.5
CCS	D5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation, Do not discharge into drains, soil or water,

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.

<sup>™</sup>Trademark of LUBREX, registered in various countries © 2005