

## **ENGINE CARE & FUEL ADDITIVES**

# Technical Data Sheet



## **DIESEL CETANE BOOSTER**

A combination of additives to improve fuel quality and fuel performance in diesel engines. Low Cetane diesel has some serious negative effects. Engines may experience hard starting, poor overall performance, high soot load, loss of power, and high emissions. These effects are amplified in cold weather. Cetane Booster raises the cetane number of diesel fuel. When added to diesel fuel, it improves fuel economy, reduces engine knock, lowers emissions, quiets engine operation, and provides easier starting at lower temperatures.

### APPLICATION:

- · Recommended for use in all diesel fuel systems
- · Recommended for Tier 4 Diesel Engines

## **FEATURES & BENEFITS:**

- · Reduces ignition delay
- · Improves diesel engine ignition
- · No environmentally harmful dyes

#### DIRECTIONS:

Pour entire contents of this bottle into fuel tank. One bottle treats up to 15 gallons (56.78 Liters) of diesel fuel

## **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

## **HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

## PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.

<sup>™</sup>Trademark of LUBREX, registered in various countries © 2005