



DIESEL SUMMER PERFORMANCE TREATMENT

Diesel Summer Performance Treatment boosts diesel fuel performance by providing injector detergency, fuel economy, smoke reduction, fuel stability, and corrosion protection. Fuel treated with Diesel Summer Performance Treatment will clean up dirty injectors, and with regular use, will keep them clean. Cleaner fuel injectors function better, resulting in reduced emissions, extended maintenance intervals, and improved fuel economy. Diesel Summer Performance Treatment also contains a cetane improver, which reduces ignition delay, knock intensity, and unburned fuel.

APPLICATION:

- Recommended for use in all diesel fuel systems
- Recommended for Tier 4 Diesel Engines


FEATURES & BENEFITS:

- Cleans fuel injectors
- Boosts cetane number
- Increases fuel economy
- Reduces smoke and emissions
- Lubricates fuel injectors
- No environmentally harmful dyes


DIRECTIONS:

Pour entire contents of this bottle into fuel tank. One bottle treats up to 15 gallons (56.78 Liters) of diesel fuel.

Dirty Injector



Clean Injector



HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.