



DRIVE 9G TRONIC 9 SPEED AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

Drive 9G-Tronic is a high-performance Automatic Transmission Fluid (ATF) formulated with latest technology synthetic base oils combined with premium quality performance additives. It's a service fill fluid for the latest generation of fuel economy optimized 9 speed automatic transmissions.

APPLICATION:

Drive 9G-Tronic is recommended for the latest generation of Mercedes-Benz 9-speed automatic transmissions (9G-tronic).

FEATURES & BENEFITS

- High thermal and oxidative stability.
- Improved lubricating
- Outstanding shear stability
- maximum reduction of fuel consumption, which reduces emission
- Superior overall performance

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- MB 236.17

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DRIVE 9G TRONIC
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	4.2
Viscosity Index	D2270	-	140
SP. Gravity @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.