



MOTO PRO ENGINE COOLANT

Pre Mixed - Long Life Coolant/Antifreeze

PRODUCT DESCRIPTION:

Moto Pro Engine Coolant is a pre-mixed ready-to-use, phosphate-free, silicate-free, nitrite-free and borate-free, ethylene glycol-based coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals. It is formulated with organic corrosion inhibitors to provide total cooling system protection for on-road and off-road use.

APPLICATION:

Moto Pro Engine Coolant is for use in all off-road vehicle cooling systems. It allows for quick fill and is hard water compatible.

FEATURES & BENEFITS:

- Specifically formulated for ORV cooling systems.
- Non abrasive formula can improve water pump seal life.
- The pre-mix formula allows for quick fill.
- Freeze protection down to -37° C
- Outstanding elastomer compatibility.

PERFORMANCE LEVELS: Meets or Exceeds:

- BS 6580
- ASTM D3306
- SAE J1034, J1038

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	MOTO PRO ENGINE COOLANT
Concentration			50%
Freezing Point	D1177	°C	-37
pH	D1278	-	8
SP. Gravity @15°C/ 60°F	D4052	g/cm3	1.06

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.